



Article number: 14104526

Dust collector pulse valve 2/2 Type 32233K series 8353K1110XA0000 aluminium/TPE 3/4" NPT

ASCO

Characteristics

Brand: ASCO
Serie: 353
Type: 32233K
Function: Normally closed (NC)
Actuation: Indirect-acting
Housing material: Aluminium
Working time: 10 % max. on 1 minute time

Options

- Membrane TPE-LT for low temperatures from -40 °C to 60 °C.
- Membraan per piece: M200697Membraan per 10 pieces: M200699

Application

- Pulse valve for dust collector systems, also for heavy duty industries.

Feature:	Value:
Orifice:	32 mm
Size process connection :	3/4" [20]
Process connection:	Internal thread (NPT)
Kvs value:	13 m³/h
Minimum pressure difference:	2 bar
Maximum pressure difference:	8.5 bar
Sealing:	NBR
Membrane material:	TPE
Medium temperature:	From -20 °C to 140°C
Ambient temperature:	From -20 °C to 85 °C

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.