


E11847



Splitter box

ProcessLine SB V4A 25m




Electrical data		
Operating voltage	[V]	10...36 DC
Protection class		III
Max. current load per module/slot	[A]	4
Max. current load total	[A]	6
Outputs		
Electrical design		PNP
Operating conditions		
Ambient temperature	[°C]	-5...70



Splitter box


ProcessLine SB V4A 25m

Protection		IP 69K; (To ensure the protection rating unused sockets must be covered with the supplied protective caps.; Tightening torque: 1,3 Nm +/- 0,1 Nm)	
Tests / approvals			
MTTF		[years]	2487
Mechanical data			
Weight		[g]	5376
Dimensions		[mm]	Ø 137.3 / L = 72
Materials		stainless steel	
Moulded-body material		stainless steel	
Number of ports splitter box		8	
Connector type		M12	
Displays / operating elements			
Display		switching status	16 x LED, yellow
		operation	1 x LED, green
Accessories			
Items supplied		Protective caps: M12	
Remarks			
Remarks		external voltage supply according to PELV	
Pack quantity		1 pcs.	
Electrical connection			
Cable: 25 m, PUR / PVC, black, Ø 11 mm; 3 x 0.75 mm² + 16 x 0.34 mm²			
Electrical connection - slot			
Connector: 8 x M12; coding: A; Moulded body: stainless steel			
			

Splitter box

ProcessLine SB V4A 25m

Connection



	Core colours :
BK =	black
BN =	brown
BU =	blue
GN =	green
GY =	grey
PK =	pink
RD =	red
VT =	lilac
WH =	white
YE =	yellow

E11847

Splitter box

ProcessLine SB V4A 25m

