

FEATURES

- High operating pressure
- RoHS compliance
- AC/DC interchangeability of the coil (10,1 W/11,6 W and 17,1 W/22,6 W)
- Valves do not require a minimum operating pressure
- Large selection of seal materials providing wide chemical compatibility
- The solenoid valves satisfy all relevant EC directives

GENERAL

Differential pressure

See «SPECIFICATIONS» [1 bar =100 kPa]

Maximum viscosity

65 cSt (mm²/s)

Response time

5 - 25 ms

fluids (*)	temperature range (TS)	seal materials (*)
air, inert gas, water, oil	-25°C to +80°C 0°C to +60°C	NBR (nitrile) UR (cast urethane)

GENERAL

MATERIALS IN CONTACT WITH FLUID

(*) Ensure that the compatibility of the fluids in contact with the materials is verified

Body	Brass	Stainless steel, AISI 304
Shading coil	Copper	Silver
Core tube	Stainless steel, AISI 305	
Core and plugnut	Stainless steel, AISI 430F	
Springs	Stainless steel, AISI 302	
Seal	NBR	
Disc	NBR or UR	
Disc holder (NO function)	PA	

ELECTRICAL CHARACTERISTICS

Coil insulation class	F (AC) or H (DC)
Connector	Spade plug (cable Ø 6-10 mm)
Connector specification	ISO 4400 / EN 175301-803, form A
Electrical safety	IEC 335
Electrical enclosure protection	Moulded IP65 (EN 60529)
Standard voltages	DC (=) : 24V - 48V
(Other voltages and 60 Hz on request)	AC (~) : 24V - 48V - 115V - 230V/50 Hz


operator ambient temperature range (TS)	power ratings				replacement coil	
	inrush ~	holding ~	hot/cold =		~	=
(°C)	(VA)	(VA)	(W)	(W)	230 V/50 Hz	24 V DC
-25 to +55	30	16	8,1	7,7/ 10,6	238213-059	238513-006
	45	20	11,1	12,5/18,6	238213-157	238513-106
	50	25	10,1	8,5/11,6	238613-059	238913-006
	70	40	17,1	15,1/22,6	238613-159	238913-106

OPTIONS


Seals and disc (*) ⁽¹⁾ (fluid temperature range)	FPM (fluoroelastomer): -15°C to +100°C (coil class F) -15°C to +120°C (coil class H) EPDM (ethylene-propylene), 0°C to +100°C CR (chloroprene), 0°C to +80°C PTFE: -15°C to +100°C (coil class F) -15°C to +120°C (coil class H)
Plug with visual indication and peak voltage suppression or with cable length of 2 m (see Solenoids, Coils & Accessories section)	

(*) Ensure that the compatibility of the fluids in contact with the materials is verified.

⁽¹⁾ The minimum ambient temperature of the solenoid valve is determined by the limitations of minimum temperature indicated.



NC function



NO function

SPECIFICATIONS

[illegible]

(1) For dimensions, see drawing(s) for each construction type on the following page(s).

(*) Ensure that the compatibility of the fluids in contact with the materials is verified

(2) UR disc only, fluid temperature 0°C to +60°C, no other elastomer can be used.

00167GB-2012/R01
Availability, design and specifications are subject to change without notice. All rights reserved.

SPECIFICATIONS

SPECIFICATIONS															15-DIGIT PRODUCT CODE									
pipe size	orifice size	flow coefficient Kv	operating pressure differential (bar)								power coil (W)		thread type	dimensions / type (1)	brass	stainless steel	voltage code							
			min.	max. (PS)													24 V/50 Hz	48 V/50 Hz	115 V/50 Hz	230 V/50 Hz	24 V/DC	48 V/DC		
	air (*)	water (*)		oil (*)	~	=	~	=	~	=	~	=												
(mm)	(m³/h)	(l/min)	~	=	~	=	~	=	~	=	~	=												
WITH MAINTAINED MANUAL OPERATOR																								
NC - Normally closed, NBR seal and disc																								
1/4	2,4	0,18	3	0	40	16	28	16	28	15	10,1	11,6	G* 02	E262K108S1N01	E262K182S1N01	FL	FR	FT	F8	H1	H9			
					NPT 02	-	8262K182S1N01																	
					49	41	28	28	28	27	17,1	22,6	G* 02	E262K109S1N01	E262K183S1N01									
					NPT 02	-	8262K183S1N01																	
	3,2	0,3	5	0	23	7,5	20	7	14	6,5	10,1	11,6	G* 02	E262K232S1N01	E262K184S1N01									
					NPT 02	-	8262K184S1N01																	
					34	17	26	17	24	15	17,1	22,6	G* 02	E262K110S1N01	E262K185S1N01									
					NPT 02	-	8262K185S1N01																	
	4	0,45	7,5	0	14	3,5	13	3,5	10	3,5	10,1	11,6	G* 02	E262K202S1N01	E262K220S1N01									
					NPT 02	-	8262K220S1N01																	
					20	7,5	14	7,5	14	7,5	17,1	22,6	G* 02	E262K112S1N01	E262K187S1N01									
					NPT 02	-	8262K187S1N01																	
	5,6	0,63	10,5	0	6,5	2	6,5	2	6,5	2	10,1	11,6	G* 02	E262K208S1N01	E262K226S1N01									
					NPT 02	-	8262K226S1N01																	
					8,5	4	8,5	4	8,5	4	17,1	22,6	G* 02	E262K114S1N01	E262K188S1N01									
					NPT 02	-	8262K188S1N01																	
	7,1	0,76	12,7	0	4	1,5	5	1,5	4	1,3	10,1	11,6	G* 02	E262K210S1N01	E262K189S1N01									
					NPT 02	-	8262K189S1N01																	
					6	3	6	3	6	3	17,1	22,6	G* 02	E262K212S1N01	E262K230S1N01									
					NPT 02	-	8262K230S1N01																	

(1) For dimensions, see drawing(s) for each construction type on the following page(s).

(*) Ensure that the compatibility of the fluids in contact with the materials is verified.

(2) UR disc only, fluid temperature 0°C to +60°C, no other elastomer can be used.

15-DIGIT PRODUCT CODE

Thread connection

G = ISO 228/1

E = ISO 228/1 & ISO 7/1 (combination thread)

8 = NPT (SAE 71051)

Product series

262

Revision letter

K = Initial release

Valves version

Voltage - class

FL = 24 V / 50 Hz - class F

FR = 48 V / 50 Hz - class F

FT = 115 V / 50 Hz - class F

F8 = 230 V / 50 Hz - class F

H1 = 24 V DC - class H

H9 = 48 V DC - class H

Options

Without manual operator

N00 = NBR disc and seals

V00 = FPM disc and seals

E00 = EPDM disc and seals

J00 = CR disc and seals

T00 = PTFE disc and seals ⁽¹⁾

⁽¹⁾ (Max. operating pressure limited to 75% of standard value)

With maintained manual operator

N01 = NBR disc and seals

V01 = FPM disc and seals

E01 = EPDM disc and seals

J01 = CR disc and seals

Electrical interface

S1 = With spade plug connector


SPARE PARTS KITS CODE (*)



		AC (~)							DC (=)						
			NBR	FPM	EPDM	CR	PTFE	NBR + UR		NBR	FPM	EPDM	CR	PTFE	NBR + UR
E262K013/019/020/021/022/023/090	M200001	N00	V00	E00	J00	T00	-	-	M200005	N00	V00	E00	J00	T00	-
E262K108/109/110/112/114	M200007	N00	V00	E00	J00	T00	-	-	M200007	N00	V00	E00	J00	T00	-
E262K130	M200017	N00	V00	E00	J00	T00	-	-	M200033	N00	V00	E00	J00	T00	-
E262K134	M200018	N00	V00	E00	J00	T00	-	-	M200033	N00	V00	E00	J00	T00	-
E262K138/142/148/152	M200018	N00	V00	E00	J00	T00	-	-	M200034	N00	V00	E00	J00	T00	-
E262K161	M200021	-	-	-	-	-	-	W00	-	-	-	-	-	-	-
E262K182/183/184/185/187/188/189	M200008	N00	V00	E00	J00	-	-	-	M200008	N00	V00	E00	J00	-	-
E262K200	M200007	-	-	-	-	-	-	W00	M200007	-	-	-	-	-	W00
E262K202/208/210/212	M200007	N00	V00	E00	J00	T00	-	-	M200007	N00	V00	E00	J00	T00	-
E262K214	M200008	-	-	-	-	-	-	W00	M200008	-	-	-	-	-	W00
E262K220/226/230	M200008	N00	V00	E00	J00	-	-	-	M200008	N00	V00	E00	J00	-	-
E262K232	M200007	N00	V00	E00	J00	T00	-	-	M200007	N00	V00	E00	J00	T00	-
E262K260	M200015	N00	V00	E00	J00	T00	-	-	M200031	N00	V00	E00	J00	T00	-
E262K261	M200016	N00	V00	E00	J00	T00	-	-	M200031	-	-	-	-	-	W00
E262K262/263/264/265	M200016	N00	V00	E00	J00	T00	-	-	M200032	N00	V00	E00	J00	T00	-
G262K001/002/014/016	M200001	N00	V00	E00	J00	T00	-	-	M200005	N00	V00	E00	J00	T00	-
G262K128	M200016	N00	V00	E00	J00	T00	-	-	M200031	N00	V00	E00	J00	T00	-
G262K129	M200016	N00	V00	E00	J00	T00	-	-	M200032	N00	V00	E00	J00	T00	-
G262K155	M200021	-	-	-	-	-	-	W00	-	-	-	-	-	-	-
G262K156	M200015	N00	V00	E00	J00	T00	-	-	M200031	N00	V00	E00	J00	T00	-
G262K168	M200021	-	-	-	-	-	-	W00	-	-	-	-	-	-	-
G262K169	M200017	N00	V00	E00	J00	T00	-	-	M200033	N00	V00	E00	J00	T00	-
G262K199	M200021	-	-	-	-	-	-	W00	-	-	-	-	-	-	-
G262K236	M200018	N00	V00	E00	J00	T00	-	-	M200033	N00	V00	E00	J00	T00	-
G262K237	M200018	N00	V00	E00	J00	T00	-	-	M200034	N00	V00	E00	J00	T00	-
8262K006/007/012/015/036/038	M200003	N00	V00	E00	J00	T00	-	-	M200005	N00	V00	E00	J00	T00	-
8262K080/086	M200003	N00	V00	E00	J00	T00	-	-	M200005	N00	V00	E00	J00	T00	-
8262K130	M200017	N00	V00	E00	J00	T00	-	-	M200033	N00	V00	E00	J00	T00	-
8262K134	M200018	N00	V00	E00	J00	T00	-	-	M200033	N00	V00	E00	J00	T00	-
8262K138/142/148/152	M200018	N00	V00	E00	J00	T00	-	-	M200034	N00	V00	E00	J00	T00	-
8262K168	M200021	-	-	-	-	-	-	W00	-	-	-	-	-	-	-
8262K169	M200017	N00	V00	E00	J00	T00	-	-	M200033	N00	V00	E00	J00	T00	-
8262K182/183/184/185/187/188/189	M200008	N00	V00	E00	J00	-	-	-	M200008	N00	V00	E00	J00	-	-
8262K199	M200021	-	-	-	-	-	-	W00	-	-	-	-	-	-	-
8262K220/226/230	M200008	N00	V00	E00	J00	-	-	-	M200008	N00	V00	E00	J00	-	-
8262K236	M200018	N00	V00	E00	J00	T00	-	-	M200033	N00	V00	E00	J00	T00	-
8262K237	M200018	N00	V00	E00	J00	T00	-	-	M200034	N00	V00	E00	J00	T00	-

(*) Ensure that the compatibility of the fluids in contact with the materials is verified.

All leaflets are available on: www.asconumatics.eu

ACCESSORIES CODE		
	Mounting bracket Steel version (AISI 1010 / 1.1121)	M200094A00
	Mounting bracket Stainless steel version (AISI 304 / 1.4301)	M200095A00

INSTALLATION

- The solenoid valves can be mounted in any position without affecting operation
- Solenoid valves have 2 mounting holes in body
- Pipe connections 1/4 (G*) have standard combination thread according to ISO 228/1 and ISO 7/1. Pipe connections G 1/8 have standard thread according to ISO 228/1
- Pipe connection identifier is 8 = NPT (SAE 71051)
- Installation/maintenance instructions are included with each valve

DIMENSIONS (mm), WEIGHT (kg)




TYPE 01

Electrical interface "S1"
Epoxy moulded
IEC 335 / ISO 4400
IP65

1/8, power coil 8,1 W / 10,6 W and 11,1 W / 18,6 W

1/4, power coil 8,1 W / 10,6 W and 11,1 W / 18,6 W



type	pipe size	A	B	C	D	E	F	G	H	X	weight ⁽¹⁾
01	1/8	91	51	30	30	43	62	71	88	26	0,30
	1/4	95	57	33	40	43	65	75	92	30	0,42

⁽¹⁾ Incl. coil(s) and connector(s).

- ① 2 mounting holes:
M5 dia., depth 6,5 mm (1/8)
M5 dia., depth 7,5 mm (1/4)
- ② Manual operator location

DIMENSIONS (mm), WEIGHT (kg)









TYPE 02

Electrical interface "S1"
Epoxy moulded
IEC 335 / ISO 4400
IP65

NC: 1/4, power coil 10,1 W / 11,6 W and 17,1 W / 22,6 W


NO: 1/8-1/4, power coil 10,1 W / 11,6 W



type	pipe size	A	B	C	D	E	F	G	H	J	K	X	weight ⁽¹⁾
02	1/8 (NO)	96	59	34	30	52	67	75	88	17,5	15	26	0,50
	1/4 (NC)	95	57	33	40	50	69	78	96	22	22	30	0,60
	1/4 (NO)	96	59	34	40	52	69	78	96	22	22	30	0,62

⁽¹⁾ Incl. coil(s) and connector(s).

- ① 2 mounting holes:
M5 dia., depth 7,5 mm (1/4)
- ② Manual operator location.



Mounting bracket

Steel or stainless steel

M200094A00 / M200095A00

