## E30072

## Welding adapter for process sensors

WELDING ADAPT G1 O-RG



1: sealing area 2: G1 Internal thread 3: sealing ring groove for O-ring  $26.0 \times 3.0$ 

## ACS EC 1935/2004 FD/A

Application		
Pressure rating	[bar]	150
Note on pressure rating	[20.]	for the connection sensor - adapter
Tests / approvals		ion and dominocation desired.
		A massible alequification to DED demands on the
Pressure Equipment Directive		A possible classification to PED depends on the application and has to be carried out by the user / operator.
Pressure Equipment Directive EAC		The adapter is intended for use in devices, machines and installations that do not fall under the categories of the technical rule TR CU 032/2013.
Safety instructions		The compatibility between medium and product material has to be checked in all applications.
Mechanical data		
Weight	[g]	292.5
Materials (wetted parts)		stainless steel (1.4404 / 316L) ; surface characteristics : Ra<0,4 / Rz 4; O-ring: FPM; O-ring: EPDM
Sensor connection		G 1 sealing cone
Process connection		welding adapter Ø 50 mm
Sealing		Gasket
Accessories		
Items supplied		O-ring: 26 x 3, EPDM, FDA compliant, E30438
		O-ring: 26 x 3, FKM, FDA compliant, E30437
Remarks		
Pack quantity		1 pcs.