



E32-D51 2M

Fiber optic sensor head, diffuse, M6 cylindrical axial, R35 heat resistant fiber, up to 150°C, 2 m cable

Specifications

Sensing method	Diffuse reflective
Shape	Threaded
Size	M6
Application	Object detection
Features	Heat-resistant
Temperature range	-40-150 °C
Sensing distance	1680 mm
Cable length	2 m
Bending radius	35 mm
Free cut	✓
Material core	Plastic
Degree of protection (IP)	IP67
Sensing surface orientation	Top-view
Material sheath	Fluororesin

Accessories



E39-F32D 1M

Spiral protective tube for E32, M6, diffuse, optical fibers, 1m



E39-F32D5 0.5M

Spiral protective tube for E32, M6, diffuse, optical fibers, 0.5 m

Related products



E3X-ZV and E3X-MZV

Smart Fiber Amplifier



E3NX-CA

High-performance color
mark sensor



E3NX-CA

High-performance color
mark sensor



E3NX-MA

Smart Fiber Amplifier Units



E3NX-FA

High-performance digital
fiber amplifier



E3X-NA

Digital fiber amplifier with
potentiometer adjustment

Downloads

CAD Library



EAC Mark removal Discontinuation Notice

EN PDF 221 KB



Fiber Sensor Selection Selection Guide

EN PDF 16.2 MB

