



## E32-DC200F4

Fiber optic sensor head, diffuse, M3 cylindrical axial with sleeve, diameter 1.2 mm, 40 mm length, R10 fiber, 2 m cable

# Specifications

<b>Sensing method</b>	Diffuse reflective
<b>Shape</b>	Sleeved
<b>Size</b>	M3
<b>Application</b>	Object detection
<b>Features</b>	Miniature
<b>Temperature range</b>	-40-70 °C
<b>Sensing distance</b>	240 mm
<b>Cable length</b>	2 m
<b>Sleeve diameter</b>	1.2 mm
<b>Sleeve length</b>	40 mm
<b>Bending radius</b>	10 mm
<b>Free cut</b>	✓
<b>Material core</b>	Plastic
<b>Degree of protection (IP)</b>	IP67
<b>Sensing surface orientation</b>	Top-view
<b>Material sheath</b>	Polyethylene

## Related products



**E3X-ZV and E3X-MZV**  
Smart Fiber Amplifier



**E3NX-CA**  
High-performance color  
mark sensor



**E3NX-CA**  
High-performance color  
mark sensor



**E3NX-MA**  
Smart Fiber Amplifier Units



**E3NX-FA**  
High-performance digital  
fiber amplifier



**E3X-NA**  
Digital fiber amplifier with  
potentiometer adjustment

## Downloads

CAD Library



**EAC Mark removal  
Discontinuation Notice**

EN PDF 221 KB



**Fiber Optic Sensors  
Group Catalogue**

EN PDF 7.54 MB

