



E32-T11R 2M

Fiber optic sensor head, through-beam, M4 cylindrical axial, R1 flexible fiber, 2 m cable

Specifications

Sensing method	Through-beam
Shape	Threaded
Size	M4
Application	Object detection
Features	Flexible fiber
Temperature range	-40-70 °C
Sensing distance	3000 mm
Cable length	2 m
Bending radius	1 mm
Free cut	✓
Material core	Plastic
Degree of protection (IP)	IP67
Sensing surface orientation	Top-view
Material sheath	PVC

Accessories



E39-F1

Long-distance lens unit for E32 through-beam fibers with M2.6 thread



E39-F2

Focal lens, side view unit for E32 through-beam optical fibers



E39-F32C 1M

Spiral protective tube for E32, M4, through-beam, optical fibers, 1m

Related products



E3X-ZV and E3X-MZV

Smart Fiber Amplifier



E3NX-CA

High-performance color
mark sensor



E3NX-CA

High-performance color
mark sensor



E3NX-MA

Smart Fiber Amplifier Units



E3NX-FA

High-performance digital
fiber amplifier



E3X-NA

Digital fiber amplifier with
potentiometer adjustment

Downloads

CAD Library



EAC Mark removal Discontinuation Notice

EN PDF 221 KB



Fiber Sensor Selection Selection Guide

EN PDF 16.2 MB

