




Connection cable

VDOG F040VAS0001E04STGH040VAS



Application

Application	hygienic and wet areas in the food industry
Free from silicone	yes

Electrical data

Operating voltage [V]	< 50 AC / < 60 DC
Protection class	III
Max. current load total [A]	3

Operating conditions

Ambient temperature [°C]	-25...80
Note on ambient temperature	cULus: ...50
Ambient temperature (moving) [°C]	5...80
Note on ambient temperature (moving)	cULus: ...50
Protection	IP 65; IP 67; IP 68; IP 69K

Mechanical data

Weight	[g]	64.6			
Dimensions	[mm]	15.5 x 15.5 x 49.5			
Materials		housing: PVC orange; Sealing: EPDM			
Material nut		stainless steel (1.4404 / 316L) / stainless steel (1.4404 / 316L)			
Drag chain suitability		bending radius for flexible use	min. 10 x cable diameter		
		travel speed	max. 3.3 m/s for a horizontal travel length of 5 m and		

EVT250



Connection cable

VDOGF040VAS0001E04STGH040VAS

		max. acceleration of 5 m/s ²		
	bending cycles		> 1 Mio.	
	torsional strain		± 180 °/m	

Remarks


Pack quantity	1 pcs.
---------------	--------

Electrical connection

Cable: 1 m, PVC, orange, Ø 4.9 mm; 4 x 0.34 mm² (42 x Ø 0.1 mm)

Electrical connection - socket

Connector: 1 x M8, straight; Locking: , stainless steel (1.4404 / 316L); Kontakte: gold-plated; Tightening torque: 0.3...0.5



Electrical connection - plug

Connector: 1 x M12, straight; Locking: , stainless steel (1.4404 / 316L); Kontakte: gold-plated; Tightening torque: 0.6...1.5



Connection

