



Certificate of Compliance

Certificate Number: LR 31928-200

Revision: LR 31928-448

Date Issued: January 28, 1994

Issued To: Omron Electronics, Inc.
One E. Commerce Dr.
Schaumburg, IL 60173

The products listed below are eligible to bear the CSA Mark.

Issued By: V. Salluce, C.E.T.
Toronto, ON Canada

Signature 

CLASS 3211 04 - INDUSTRIAL CONTROL EQUIPMENT - Motor Controllers - Magnetic

PRODUCTS

Relays. Type C6C, (with suffixes), open, with dust cover or plastic seal, silver cadmium oxide or silver indium oxide contacts, rated 1 pole, 10A, 250 or 30V dc, 1/6 hp, 125V ac, 1/4 hp, 125 or 250V ac, 1/3 hp, 125 or 250V ac, 3300 (silver cadmium oxide contacts), 330 VA, 115 to 250V ac, 530 VA, 20-265V ac, 60VA, 4.5-30V dc, 4 FLA, 30V dc, (Ag Cd only); 2-pole, 8A, 250V ac or 30V dc, 1/6 hp, 125V ac, 1/4 hp, 125 or 250V ac and 1/3 hp, 125 or 250V ac, 330VA, 250V ac, 330VA, 20-265V ac, 60VA, 4.5-30V dc, 4 FLA, 30V dc, (Ag Cd only); with Suffix "CN" (at ambient of 80C) for 1- and 2-pole models; 1/6 hp, 125V ac, 1/4 hp, 125/250V ac, 1/3 hp, 125/250V ac, 600WT, 120V ac Tungsten; 530VA; 20-265V ac, 2A max pilot duty, 432VA, 30V dc pilot duty, 3.6 FLA, 22 LRA, 30V dc pilot duty; Type G6CU-1114P-FD-US rated 800 W, 120 V ac ballast; 1200 W, 277 V ac ballast; 800 W 120 V ac tungsten (at 40C ambient max); coils, 3 to 60V dc.