


## Inductive sensor

IIKC014BASKG/M/V4A/10M



## Product characteristics

|                    |                    |
|--------------------|--------------------|
| Electrical design  | PNP/NPN            |
| Output function    | normally open      |
| Sensing range [mm] | 14                 |
| Housing            | threaded type      |
| Dimensions [mm]    | M30 x 1.5 / L = 81 |

## Application

|                 |                                              |
|-----------------|----------------------------------------------|
| Special feature | Increased sensing range; Optical setting aid |
| Application     | regular cleaning processes                   |

## Electrical data

|                             |                                  |
|-----------------------------|----------------------------------|
| Operating voltage [V]       | 10...36 DC                       |
| Current consumption [mA]    | < 10; (only in 3-wire operation) |
| Protection class            | II                               |
| Reverse polarity protection | yes                              |

## Outputs

|                                                      |                                 |
|------------------------------------------------------|---------------------------------|
| Electrical design                                    | PNP/NPN                         |
| Output function                                      | normally open                   |
| Max. voltage drop switching output DC [V]            | 2.5                             |
| Minimum load current [mA]                            | 2; (only in 2-wire operation)   |
| Max. leakage current [mA]                            | 0.5; (only in 2-wire operation) |
| Permanent current rating of switching output DC [mA] | 100                             |
| Switching frequency DC [Hz]                          | 100                             |
| Short-circuit protection                             | yes                             |
| Type of short-circuit protection                     | pulsed                          |
| Overload protection                                  | yes                             |

## Detection zone

|                    |    |
|--------------------|----|
| Sensing range [mm] | 14 |
|--------------------|----|



## Inductive sensor

IIKC014BASKG/M/V4A/10M

|                         |      |           |
|-------------------------|------|-----------|
| Real sensing range Sr   | [mm] | 14 ± 10 % |
| Operating distance      | [mm] | 0...11.34 |
| Increased sensing range |      | yes       |

## Accuracy / deviations

|                    |           |                                                                             |
|--------------------|-----------|-----------------------------------------------------------------------------|
| Correction factor  |           | steel: 1 / stainless steel: 0.7 / brass: 0.5 / aluminium: 0.4 / copper: 0.3 |
| Hysteresis         | [% of Sr] | 3...15                                                                      |
| Switch point drift | [% of Sr] | -10...10                                                                    |

## Operating conditions

|                     |      |               |
|---------------------|------|---------------|
| Ambient temperature | [°C] | 0...100       |
| Protection          |      | IP 68; IP 69K |

## Tests / approvals

|             |                           |                                |
|-------------|---------------------------|--------------------------------|
| EMC         | EN 61000-4-2 ESD          | 4 kV CD / 8 kV AD              |
|             | EN 61000-4-3 HF radiated  | 10 V/m                         |
|             | EN 61000-4-4 Burst        | 2 kV                           |
|             | EN 61000-4-5 Surge        | 0,5 kV line to line, Ri: 2 Ohm |
|             | EN 61000-4-6 HF conducted | 10 V                           |
|             | EN 55011                  | class B                        |
| MTTF        | [years]                   | 1479                           |
| UL approval | Ta                        | 0...40 °C                      |
|             | Enclosure type            | Type 1                         |
|             | power supply              | Limited Voltage/Current        |
|             | File number UL            | E174191                        |

## Mechanical data

|                    |      |                                                     |
|--------------------|------|-----------------------------------------------------|
| Weight             | [g]  | 456.8                                               |
| Housing            |      | threaded type                                       |
| Mounting           |      | flush mountable                                     |
| Dimensions         | [mm] | M30 x 1.5 / L = 81                                  |
| Thread designation |      | M30 x 1.5                                           |
| Materials          |      | stainless steel (1.4404 / 316L); sensing face: PEEK |

## Displays / operating elements

|                     |                  |                     |
|---------------------|------------------|---------------------|
| Display             | switching status | 4 x 90° LED, yellow |
|                     | setting aid      | 1 x LED, red        |
| Optical setting aid |                  | yes                 |

## Accessories

|                |  |              |
|----------------|--|--------------|
| Items supplied |  | lock nuts: 2 |
|----------------|--|--------------|

## Remarks

|               |  |                                                  |
|---------------|--|--------------------------------------------------|
| Remarks       |  | suitable for PLC type 1 according to IEC 61131-2 |
| Pack quantity |  | 1 pcs.                                           |



## Inductive sensor

IIC014BASKG/M/V4A/10M

### Electrical connection

Cable: 10 m, PVC; 3 x 0.34 mm<sup>2</sup>

### Connection

