


Capacitive sensor

KI-2015-BBOA/NI/HUBBELL



Product characteristics

Output function	normally closed
Sensing range [mm]	3...15
Housing	threaded type
Dimensions [mm]	M30 x 1.5 / L = 81

Electrical data

Operating voltage [V]	20...125 AC/DC
Protection class	II
Reverse polarity protection	no
Max. power-on delay time [ms]	300

Outputs

Output function	normally closed
Max. voltage drop switching output DC [V]	8
Max. voltage drop switching output AC [V]	10
Minimum load current [mA]	5
Max. leakage current [mA]	1.7 (125 V AC) / 1.5 (24 V DC)
Permanent current rating of switching output AC [mA]	200; (>70°C; 250 mA: >50°C)
Permanent current rating of switching output DC [mA]	200; (>70°C; 250 mA: >50°C)
Short-time current rating of switching output [mA]	2200; (20 ms / 0,5 Hz)
Switching frequency AC [Hz]	25
Switching frequency DC [Hz]	40
Short-circuit proof	no
Overload protection	no

Detection zone

Sensing range [mm]	3...15
Sensing range adjustable	yes
Factory setting sensing range [mm]	15
Real sensing range Sr [mm]	15 ± 10 %



Capacitive sensor

KI-2015-BBOA/NI/HUBBELL

Operating distance	[mm]	0...12.1
Accuracy / deviations		
Correction factor		glass: 0.4 / water: 1 / ceramics: 0.2 / PVC: 0.2
Hysteresis	[% of Sr]	1...15
Switch point drift	[% of Sr]	-15...15
Operating conditions		
Ambient temperature	[°C]	-25...70
Protection		IP 65
Increased immunity		yes; (increased immunity to conducted radio frequency interference)
Tests / approvals		
EMC		EN 60947-5-2
Mechanical data		
Weight	[g]	193.2
Housing		threaded type
Mounting		non-flush mountable
Dimensions	[mm]	M30 x 1.5 / L = 81
Thread designation		M30 x 1.5
Materials		PBT
Displays / operating elements		
Display	switching status	1 x LED, yellow
Electrical connection		
Required protection		miniature fuse to IEC60127-2 sheet 1; ≤ 2 A; fast acting
Accessories		
Items supplied		lock nuts: 2
		screwdriver: 1
Remarks		
Remarks		Recommendation: Check the safe functioning of the unit after a short circuit. The requirements regarding the protection rating of the connection / connector are to be checked and ensured by the user
Pack quantity		1 pcs.

Capacitive sensor

KI-2015-BBOA/NI/HUBBELL

Electrical connection

Cable: 2 m, PVC; 2 x 0.5 mm²

Connection



Connector: 1 x Hubbell (HBL7465V)



Connection

