




## Dial Gauge, Lug Back, ISO Type

Item number: 1013A-10

### Images



### Description

#### Compact Type 1 and 3,5 mm Range Small Diameter - Metric


This is a compact, dial indicator with a bezel  $\varnothing$  40 mm. It offers you the following benefits:

- It is ideal for use in applications where space is limited.

Specification

|                          |                                         |
|--------------------------|-----------------------------------------|
| Digital/Analog:          | Analog                                  |
| Inch-Metric:             | Metric                                  |
| Delivered:               | With certificate of inspection          |
| Range:                   | 1 mm                                    |
| Range per rev.:          | 0,2 mm                                  |
| Dial reading:            | 0-100-0                                 |
| Graduation:              | 0.002 mm                                |
| MPE any 1/10 revolution: | 2.5 µm                                  |
| MPE any 1/2 revolution:  | 4 µm                                    |
| MPE any 1 revolution:    | 4.5 µm                                  |
| MPE measuring range:     | 6 µm                                    |
| H MPE (Hysteresis):      | 2 µm                                    |
| R MPE (Repeatability):   | 1 µm                                    |
| Measuring force:         | 0,4-1,5 N                               |
| Mass:                    | 95 g                                    |
| Stem:                    | 8 mm                                    |
| Contact point:           | Carbide tipped, thread: M 2.5 x 0.45 mm |
| Balanced dial:           | Yes                                     |
| Shockproof:              | Yes                                     |
| Type:                    | EN ISO Standard                         |

Dimensions



**A:** 32.5 mm

**B:** 49 mm

**C:** 40 mm

**D:** 15 mm

**E:** 20 mm

**F:** 13.8 mm

**G:** 15.2 mm

**H:** 38 mm

**I:** 6.6 mm

Accessories

**Optional accessories:**

---

**Limit Hands (Green) 2 pcs.**

Dial Indicator Series 1, Test Indicator  
Art No. 21AAB363

**Bezel Clamp for Dial Gauge**

Series 1  
Art No. 21RZA149

**Spindle Lifting Lever**

for S-Type and A-Type Serie 1  
Art No. 902100  
£8.20 ex. VAT

**Spindle Lifting Cable**

for Indicator, L=500mm  
Art No. 21JZA295



### Spindle Lifting Cable with Auto Stop

for Indicator, L=300mm  
Art No. 21JZA301

#### Spare parts

##### Consumable spares:



### Contact Element Ball Point, M2,5x0,45

7,3mm Length, Carbide, Metric  
Art No. 901312  
**£7.70** ex. VAT