




Dial Gauge, Lug Back, ANSI/AGD Type

Item number: 1044A-01

Images



Specification

Digital/Analog:	Analog
Inch-Metric:	Metric
Delivered:	With certificate of inspection, bezel clamp
Range:	5 mm
Range per rev.:	1 mm
Dial reading:	±0-100
Graduation:	0,01 mm
MPE first one revolution:	±10 µm
MPE first 2 1/2 revolutions:	±10 µm
MPE > 2 1/2-10 revolutions:	±13 µm
H MPE (Hysteresis):	3 µm
R MPE (Repeatability):	±3 µm
Type:	ANSI/AGD Standard
Measuring force:	0,4-1,4 N
Stem:	9.52 mm / 0.375"
Contact point:	Carbide tipped, thread: 4-48UNF

Accessories

Optional accessories:

**Limit Hands (Green) 2 pcs.**

Dial Indicator Series 1, Test Indicator
Art No. 21AAB363

**Spindle Lifting Lever**

for S-Type and A-Type Serie 1
Art No. 902100
£8.20 ex. VAT

**Spindle Lifting Cable**

for Indicator, L=500mm
Art No. 21JZA295

**Spindle Lifting Cable with Auto Stop**

for Indicator, L=300mm
Art No. 21JZA301

Standard accessories:



Bezel Clamp for Dial Gauge

Series 1

Art No. 21RZA149

Spare parts

Consumable spares:



Contact Element Ball Point, 4-48UNF

1/4" Length, Carbide, Inch

Art No. 21BZB005

£8.60 ex. VAT