



Dial Gauge, Lug Back, ISO Type

Item number: 1044A-15

Images



Description

Compact Type 5 mm Range Small Diameter - Metric

This is a compact, dial indicator with a bezel $\varnothing$ 40 mm. It offers you the following benefits:



- It is ideal for use in applications where space is limited.

Specification

Digital/Analog:	Analog
Inch-Metric:	Metric
Delivered:	With certificate of inspection
Range:	5 mm
Range per rev.:	1 mm

Dial reading:	±0-100
Graduation:	0.01 mm
MPE any 1/10 revolution:	5 µm
MPE any 1/2 revolution:	9 µm
MPE any 1 revolution:	10 µm
MPE measuring range:	12 µm
H MPE (Hysteresis):	3 µm
R MPE (Repeatability):	3 µm
Measuring force:	0,1-0,4 N
Mass:	90 g
Stem:	8 mm
Contact point:	Carbide tipped, thread: M 2.5 x 0.45 mm
Continuous dial:	Yes
Type:	EN ISO Standard

Dimensions

**A:** 32.5 mm**B:** 47.5 mm**C:** 40 mm**D:** 15 mm**E:** 20 mm**F:** 13.8 mm**G:** 13.7 mm**H:** 38 mm**I:** 6.6 mm**A:** 32.5 mm**B:** 47.5 mm**C:** 40 mm**D:** 15 mm**E:** 20 mm**F:** 13.8 mm**G:** 13.7 mm**H:** 38 mm**I:** 6.6 mm

Accessories

Optional accessories:



Limit Hands (Green) 2 pcs.

Dial Indicator Series 1, Test Indicator
Art No. 21AAB363



Bezel Clamp for Dial Gauge

Series 1
Art No. 21RZA149

Spindle Lifting Lever

for S-Type and A-Type Serie 1
Art No. 902100
£8.20 ex. VAT



Spindle Lifting Cable

for Indicator, L=500mm
Art No. 21JZA295



Spindle Lifting Cable with Auto Stop

for Indicator, L=300mm
Art No. 21JZA301



Spare parts

Consumable spares:



Contact Element Ball Point, M2,5x0,45

7,3mm Length, Carbide, Metric
Art No. 901312
£7.70 ex. VAT