



Dial Indicator, Flat Back

Item number: 1044SB-60

Images



Description

Compact Type 1 and 3,5 mm Range Small Diameter - Metric

This is a compact, dial indicator with a bezel Ø 40 mm. It offers you the following benefits:


- It is ideal for use in applications where space is limited.

Specification

Digital/Analog:	Analog
Inch-Metric:	Metric
Functions:	ISO type
Delivered:	with certificate of inspection, limit indicators
Range:	5 mm
Range per rev.:	1 mm
Graduation:	0.01 mm

MPE any 1/10 revolution:	5 μm
MPE any 1/2 revolution:	9 μm
MPE any 1 revolution:	10 μm
MPE measuring range:	12 μm
H MPE (Hysteresis):	3 μm
R MPE (Repeatability):	3 μm
Mass:	70 g
Stem:	8 mm
Contact point:	Carbide tipped, thread: M 2.5 x 0.45 mm

Dimensions



A: 32.5 mm

B: 57 mm

C: 40 mm

D: 14.5 mm

E: 20 mm

F: 12.2 mm

G: 24.8 mm

I: 6.6 mm

I: 6.6 mm

Accessories

Optional accessories:



Limit Hands (Green) 2 pcs.

Dial Indicator Series 1, Test Indicator
Art No. 21AAB363



Bezel Clamp for Dial Gauge

Series 1
Art No. 21RZA149



Spindle Lifting Lever

for S-Type and A-Type Serie 1
Art No. 902100
£8.20 ex. VAT



Spindle Lifting Cable

for Indicator, L=500mm
Art No. 21JZA295



Spindle Lifting Cable with Auto Stop

for Indicator, L=300mm
Art No. 21JZA301

Spare parts

Consumable spares:



**Contact Element Ball Point,
M2,5x0,45**

7,3mm Length, Carbide, Metric

Art No. 901312

£7.70 ex. VAT