




Dial Gauge, Flat Back,
ANSI/AGD Type

Item number: 2047A-11

Images



Specification

Digital/Analog:	Analog
Inch-Metric:	Metric
Delivered:	With certificate of inspection, bezel clamp
Range:	10 mm
Range per rev.:	1 mm
Dial reading:	0-50-0
Graduation:	0,01 mm
MPE first one revolution:	±10 µm
MPE first 2 1/2 revolutions:	±10 µm
MPE > 2 1/2-10 revolutions:	±13 µm
H MPE (Hysteresis):	3 µm
R MPE (Repeatability):	±3 µm
Type:	ANSI/AGD Standard
Measuring force:	0,4-1,4 N

Stem:	9.52 mm / 0.375"
Contact point:	Carbide tipped, thread: 4-48UNF

Accessories

Optional accessories:	
	Limit Hands (green) 2pcs Dial Indicator Series 2/3/4 Art No. 21AZB195
	Spindle Lifting Lever for Digital Indicator, A-Type Dial Indicator Serie 2/3/4 Art No. 21EZA198 £7.70 ex. VAT
	Spindle Lifting Cable for Indicator, L=500mm Art No. 21JZA295
	Spindle Lifting Cable with Auto Stop for Indicator, L=300mm Art No. 21JZA301
Standard accessories:	



Bezel Clamp for Dial Gauge

Inch, Series 2/3/4
Art No. 21RZA065
£2.30 ex. VAT

Spare parts

Consumable spares:



Contact Element Ball Point, 4-48UNF

1/4" Length, Carbide, Inch
Art No. 21BZB005
£8.60 ex. VAT