




Dial Gauge, Lug Back, ISO Type

Item number: 2110A-70

Images



Description

Standard Type, 1 mm Range, 0,001 mm Graduation

This is a standard dial indicator. It offers you the following benefits:

- Bezel clamp and lifting lever (optional) can be attached to either right or left side. They can be easily installed and removed without tools.
- No through screw holes on the frame and secure adhesion between the bezel and the crystal as well as the use of an O-ring prevents water or oil penetration.


Features

Digital/Analog:

Analog

Inch-Metric:	Metric
Type:	EN ISO Standard
Delivered:	With certificate of inspection
Range:	1 mm
Range per rev.:	0,1 mm
Dial reading:	±0-100
Graduation:	0.001 mm
MPE any 1/10 revolution:	2.5 µm
MPE any 1/2 revolution:	4 µm
MPE any 1 revolution:	4.5 µm
MPE measuring range:	5 µm
H MPE (Hysteresis):	2 µm
R MPE (Repeatability):	1 µm
Measuring force:	0,4-2 N
Mass:	150 g
Stem:	8 mm
Contact point:	Carbide tipped, thread: M 2.5 x 0.45 mm
Continuous dial:	Yes
Double scale spacing:	Yes
Shockproof:	Yes

Dimensions



A: 47,2 mm
B: 67.5 mm
C: 57 mm
D: 18.1 mm
E: 20 mm
F: 12.3 mm
G: 26.7 mm
H: 52 mm
I: 7.6 mm

Accessories

Optional accessories:



Limit Hands (green) 2pcs

Dial Indicator Series 2/3/4

Art No. 21AZB195

Price on application



Bezel Clamp for Dial Gauge

Metric, Series 2/3/4

Art No. 21AZB148

Price on application



Spindle Lifting Lever

for Digital Indicator, A-Type Dial Indicator

Serie 2/3/4

Art No. 21EZA198

Price on application

Spare parts

Consumable spares:



Contact Element Ball Point, M2,5x0,45

7,3mm Length, Carbide, Metric

Art No. 901312

Suggested retail price: 14.00 €*



NBR Rubber Boot

Digital Gauge ID-B, Dial Gauge IP63/IP64

Art No. 21AAB562

Suggested retail price: **1.60 €***