



Dial Gauge, Flat Back, ISO Type

Item number: 2119AB-10

Images



Description

Standard Type, 2 and 5 mm Range, 0,001 / 0,005 mm Graduation

This is a standard dial indicator. It offers you the following benefits:


- Bezel clamp and lifting lever (optional) can be attached to either right or left side. They can be easily installed and removed without tools.
- No through screw holes on the frame and secure adhesion between the bezel and the crystal as well as the use of an O-ring prevents water or oil penetration.

Specification

Digital/Analog:	Analog
Inch-Metric:	Metric
Type:	EN ISO Standard
Delivered:	With certificate of inspection
Range:	5 mm
Range per rev.:	0,2 mm
Dial reading:	0-100-0
Graduation:	0.001 mm
MPE any 1/10 revolution:	4 µm
MPE any 1/2 revolution:	6 µm

MPE any 1 revolution:	6.5 µm
MPE measuring range:	10 µm
H MPE (Hysteresis):	2.5 µm
R MPE (Repeatability):	2.0 µm
Measuring force:	0,4-1,5 N
Mass:	137 g
Stem:	8.0 mm
Contact point:	Carbide tipped, thread: M 2.5 x 0.45 mm
Balanced dial:	Yes

Dimensions



A: 47.2 mm

B: 60.7 mm

C: 57 mm

D: 18.1 mm

E: 20 mm

F: 16.9 mm

G: 15.3 mm

H: 52 mm

I: 7.6 mm

Accessories

Optional accessories:



Limit Hands (green) 2pcs

Dial Indicator Series 2/3/4
Art No. 21AZB195



Bezel Clamp for Dial Gauge

Metric, Series 2/3/4
Art No. 21AZB148



Spindle Lifting Lever

for Digital Indicator, A-Type Dial Indicator
Serie 2/3/4
Art No. 21EZA198
£7.70 ex. VAT



Spindle Lifting Knob

for 12,7mm Range
Art No. 21EZA105
£19.44 inc. VAT
£16.20 ex. VAT

Spare parts

Consumable spares:



Contact Element Ball Point, M2,5x0,45

7,3mm Length, Carbide, Metric
Art No. 901312
£7.70 ex. VAT