



Dial Indicator, Flat Back

Item number: 2330SB-10

Images



Description

Standard Type, 30 mm Range, 0,01 mm Graduation

This is a standard dial indicator. It offers you the following benefits:


- Bezel clamp and lifting lever (optional) can be attached to either right or left side. They can be easily installed and removed without tools.
- No through screw holes on the frame and secure adhesion between the bezel and the crystal as well as the use of an O-ring prevents water or oil penetration.

Specification

Digital/Analog:	Analog
Inch-Metric:	Metric
Functions:	ISO type
Delivered:	with certificate of inspection, limit indicators
Range:	30 mm
Range per rev.:	1 mm
Graduation:	0.01 mm

MPE any 1/10 revolution:	7 μm
MPE any 1/2 revolution:	11 μm
MPE any 1 revolution:	12 μm
MPE measuring range:	25 μm
H MPE (Hysteresis):	5 μm
R MPE (Repeatability):	3 μm
Mass:	141 g
Stem:	8 mm
Contact point:	Carbide tipped, thread: M 2.5 x 0.45 mm
Continuous dial:	Yes
Coaxial revolution counter:	Yes
Cushioned end point:	Yes

Dimensions



mm

A: 38.8 mm

B: 88.7 mm

C: 57 mm

D: 17.7 mm

E: 20 mm

F: 16.9 mm

G: 43.3 mm

I: 7.6 mm

I: 7.6 mm

Accessories

Optional accessories:



Limit Hands (green) 2pcs

Dial Indicator Series 2/3/4
Art No. 21AZB195



Bezel Clamp for Dial Gauge

Metric, Series 2/3/4
Art No. 21AZB148

Spare parts

Consumable spares:



Contact Element Ball Point, M2,5x0,45

7,3mm Length, Carbide, Metric
Art No. 901312
£7.70 ex. VAT