



Dial Gauge, Lug Back,
ANSI/AGD Type

Item number: 2424A-19

Images



Description

This is a standard, inch dial indicator. It offers you the following benefits:


- Bezel clamp and lifting lever (optional) can be attached to either right or left side. They can be easily installed and removed without tools.
- No through screw holes on the frame and secure adhesion between the bezel and the crystal as well as the use of an O-ring prevents water or oil penetration.

Specification

Digital/Analog:	Analog
Inch-Metric:	Inch
Delivered:	With certificate of inspection, bezel clamp
Range:	2 "
Range per rev.:	0,1"
Dial reading:	±0.0-100.0
Graduation:	0,001"
H MPE (Hysteresis):	0,00033"
R MPE (Repeatability):	±0,0002"
MPE first one revolution:	±0,001"
MPE first 2 1/2 revolutions:	±0,001"

MPE > 2 1/2-10 revolutions:	±0,002"
MPE > 10-20 revolutions:	±0,003"
Type:	ANSI/AGD Standard
Measuring force:	0,4-2,5 N
Mass:	250 g
Stem:	9.52 mm / 0.375"
Contact point:	Carbide tipped, thread: 4.0-48.0UNF
Continuous dial:	Yes
Coaxial revolution counter:	Yes
Cushioned end point:	Yes
Shockproof:	Yes

Dimensions



A: 4.65 inch

B: 5.61 inch

C: 2.24 inch

D: 0.71 inch

E: 5/6 inch

F: 2.14 inch

G: 2.35 inch

H: 2.05 inch

I: 0.37 inch

Accessories

Optional accessories:



Limit Hands (green) 2pcs

Dial Indicator Series 2/3/4

Art No. 21AZB195

Standard accessories:




Bezel Clamp for Dial Gauge

Inch, Series 2/3/4
Art No. 21RZA065
£2.30 ex. VAT

Spare parts

Consumable spares:



Contact Element Ball Point, 4-48UNF

1/4" Length, Carbide, Inch
Art No. 21BZB056
£4.10 ex. VAT