



Dial Indicator, Flat Back

Item number: 2972TB

Images



Description

Lightweight type

This is a one revolution dial indicator. It offers you the following benefits:


- Excellent water and drip-proof characteristics
- It eliminates the possibility of reading errors due to miscounting multiple revolutions.

Specification

Digital/Analog:	Analog
Inch-Metric:	Metric
Functions:	ISO type
Delivered:	with certificate of inspection, limit indicators
Range:	1 mm
Plunger Stroke:	3.5 mm

Range per rev.:	1.4 mm
Graduation:	0.01 mm
MPE any 1/10 revolution:	5 µm
MPE measuring range:	7 µm
H MPE (Hysteresis):	3 µm
R MPE (Repeatability):	3 µm
Mass:	75 g
Stem:	8 mm
Contact point:	Carbide tipped, thread: M 2.5 x 0.45 mm
One revolution:	Yes
Cushioned end point:	Yes
Shockproof:	Yes

Dimensions



- A: 43.2 mm
- B: 66 mm
- C: 57 mm
- D: 16.5 mm
- F: 21 mm
- G: 17.2 mm
- I: 7.6 mm
- L: 7.6 mm

Accessories

Optional accessories:



Limit Hands (green) 2pcs

Dial Indicator Series 2/3/4
Art No. 21AZB195

Self-tapping Screw for Plastic

For Dial Gauge
Art No. 546666



Spare parts

Consumable spares:



Contact Element Ball Point, M2,5x0,45

7,3mm Length, Carbide, Metric
Art No. 901312
£7.70 ex. VAT