




Dial Test Indicator, Horizontal Type

Item number: 513-402-10E

Images



Description


A Mitutoyo versatile anti-magnetic type lever indicator (or dial test indicator, DTI) suited to alignment operations on machine tools and similar applications. This indicator automatically adapts to the required measuring direction on contact, and the jewelled movement provides lowest friction and stiction for smooth and precise operation. Supplied with a basic set of mounting accessories.

Features

Digital/Analog:	Analog
Inch-Metric:	Inch
Delivered:	In a box with stem $\varnothing 3/8"$ (9,52 mm), stylus $\varnothing 0,079"$
Range:	0,03 "
Dial reading:	0-15-0
Graduation:	0.0005"

H MPE (Hysteresis):	0,0002"
R MPE (Repeatability):	±0,0002"
MPE first one revolution:	±0,0005"
Measuring force:	0,01-0,3 N
Carbide stylus tip ø2 mm No.:	133195
Mass:	40 g
Contact point:	Thread M 1.7 x 0.35
Remarks:	Basic set

Dimensions



Accessories

Optional accessories:



Limit Hands (Green) 2 pcs.

Dial Indicator Series 1, Test Indicator
Art No. 21AAB363
Price on application

Standard accessories:



Point Dia 2mm/513

L=0.76"
Art No. 133195
Price on application



Knurled Clamp Ring for Stem

Lever Indicator Serie 513

Art No. 190322

Suggested retail price: 12.00 €*
