




Dial Test Indicator, Vertical Type

Item number: 513-452-10E

Images



Description


A Mitutoyo versatile anti-magnetic lever indicator (or dial test Indicator DTI) suited to alignment operations on machine tools and similar applications. This indicator automatically adapts to the required measuring direction on contact, and the jewelled movement provides lowest friction and stiction for smooth and precise operation. Supplied with a basic set of mounting accessories.

Specification

Digital/Analog:	Analog
Inch-Metric:	Inch
Delivered:	In a box with stem $\varnothing 3/8"$ (9.52 mm), stylus $\varnothing 0.079"$
Range:	0,03 "

Dial reading:	0-15-0
Graduation:	0.0005"
H MPE (Hysteresis):	0.0002"
R MPE (Repeatability):	±0.0002"
MPE first one revolution:	±0.0005"
Measuring force:	0,01-0,3 N
Mass:	50 g
Contact point:	Thread M 1.7 x 0.35
Remarks:	Basic set

Dimensions



Accessories

Optional accessories:



Limit Hands (Green) 2 pcs.

Dial Indicator Series 1, Test Indicator
Art No. 21AAB363

Standard accessories:

Art No. 21CAB105



Knurled Clamp Ring for Stem

Lever Indicator Serie 513

Art No. 190322

£4.50 ex. VAT



Point Dia 2mm/513

L=0.76"

Art No. 133195

