




Dial Test Indicator, Pocket Type

Item number: 513-514-10E

Images



Full set

Swivel clamp
900321
for ø4 mm, ø5 mm, dovetail

Metric holding bar
(L 100 mm)

Stem,
ø4 mm

ø8 mm
holding rod
and
900211

Basic set

Stylus, ø2 mm
carbide point

Indicator

Stem,
ø8 mm


Spanner **301336**

This is a small type Dial Test Indicator (Lever Type) which offers you the following benefits:

Specification

Digital/Analog:	Analog
Inch-Metric:	Metric
Delivered:	In a box with stem ø8 mm, stylus ø2 mm
Range:	0.5 mm
Dial reading:	0-25-0
Graduation:	0.01 mm
H MPE (Hysteresis):	4 mm
MPE any 10 scale divisions:	5 µm
MPE measuring range:	10 µm
R MPE (Repeatability):	3 µm
Measuring force:	≤ 0,3 N
Carbide stylus tip ø2 mm No.:	131324
Contact point:	Thread M 1.7 x 0.35
Remarks:	Basic set

Dimensions



Accessories

Optional accessories:**Limit Hands (Green) 2 pcs.**

Dial Indicator Series 1, Test Indicator
Art No. 21AAB363

Standard accessories:**Stem for Serie 513**

D= 8mm
Art No. 102822
£4.20 ex. VAT

**Stylus for Series 513**

D=2mm, 36,8mm length, Carbide
Art No. 129949
£11.30 ex. VAT

**Spanner R=7,3/4,5mm**

Micrometer
Art No. 301336
£2.00 ex. VAT

