




PN7093

PN-025-RER14-QFRKG/US/ IV



Pressure sensors



- 1: 4-digit alphanumeric display / alternating indication of red and green  
2: LEDs (display unit / switching status)  
3: Programming button  
4: Upper part of the housing can be rotated by 345°



Product characteristics

Electronic pressure monitor

M12 connector

Function programmable

Measuring element: ceramic-capacitive pressure measuring cell

Process connection: G 1/4 I

2 outputs

OUT1 = switching output

OUT2 = switching output

4-digit alphanumeric display / alternating indication of red and green

Measuring range: 0...25 bar / 0...363 psi / 0...2.5 MPa

Application

Application

Type of pressure: relative pressure  
Group 2 fluids according to the Pressure Equipment Directive (PED),  
group 1 fluids on request  
For gas applications > 25 bar: select PN7x7x series

|                         |          |          |        |
|-------------------------|----------|----------|--------|
| Pressure rating         | 150 bar  | 2175 psi | 15 MPa |
| Bursting pressure min.  | 350 bar  | 5075 psi | 35 MPa |
| Medium temperature [°C] | -25...80 |          |        |

Electrical data

Electrical design

DC PNP/NPN

Operating voltage [V]

18...30 DC <sup>1)</sup>

Current consumption [mA]

< 35

Insulation resistance [MΩ]

> 100 (500 V DC)

Protection class

III

Reverse polarity protection

yes

Outputs

Output

2 outputs

OUT1 = switching output

OUT2 = switching output

Output function

2 x normally open / closed programmable

Current rating [mA]

150; 200 (...60 °C); 250 (...40 °C)

Voltage drop [V]

< 2.5

Short-circuit protection

pulsed


Overload protection

yes

# PN7093 - Electronic pressure monitor - eclass: 27201302 / 27-20-13-02

|                                                                                                    |                                                                                                    |             |                 |
|----------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------|-------------|-----------------|
| Switching frequency [Hz]                                                                           | ≤ 170                                                                                              |             |                 |
| Measuring / setting range                                                                          |                                                                                                    |             |                 |
| Measuring range                                                                                    | 0...25 bar                                                                                         | 0...363 psi | 0...2.5 MPa     |
| Setting range                                                                                      |                                                                                                    |             |                 |
| Set point, SP                                                                                      | 0.2...25 bar                                                                                       | 4...362 psi | 0.02...2.5 MPa  |
| Reset point, rP                                                                                    | 0.1...24.9 bar                                                                                     | 2...360 psi | 0.01...2.49 MPa |
| in steps of                                                                                        | 0.1 bar                                                                                            | 2 psi       | 0.01 MPa        |
| Accuracy / deviations                                                                              |                                                                                                    |             |                 |
| Accuracy / deviations (in % of the span)                                                           |                                                                                                    |             |                 |
| Switch point accuracy                                                                              | < ± 0.5                                                                                            |             |                 |
| Characteristics deviation *)                                                                       | < ± 0.25 (BFSL) / < ± 0.5 (LS)                                                                     |             |                 |
| Hysteresis                                                                                         | < ± 0.25                                                                                           |             |                 |
| Repeatability **)                                                                                  | < ± 0.1                                                                                            |             |                 |
| Long-term stability ***)                                                                           | < ± 0.05                                                                                           |             |                 |
| Temperature coefficients (TEMPCO) in the temperature range -25...80° C (in % of the span per 10 K) |                                                                                                    |             |                 |
| Greatest TEMPCO of the zero point                                                                  | 0.2                                                                                                |             |                 |
| Greatest TEMPCO of the span                                                                        | 0.2                                                                                                |             |                 |
| Reaction times                                                                                     |                                                                                                    |             |                 |
| Power-on delay time [s]                                                                            | < 0.3                                                                                              |             |                 |
| Min. response time switching output [ms]                                                           | < 3                                                                                                |             |                 |
| Delay time programmable dS, dr [s]                                                                 | 0...50                                                                                             |             |                 |
| Integrated watchdog                                                                                | yes                                                                                                |             |                 |
| Software / programming                                                                             |                                                                                                    |             |                 |
| Programming options                                                                                | hysteresis / window function; NO / NC; output polarity; on delay, off delay; damping; display unit |             |                 |
| Interfaces                                                                                         |                                                                                                    |             |                 |
| IO-Link device                                                                                     |                                                                                                    |             |                 |
| Transfer type                                                                                      | COM2 (38.4 kBaud)                                                                                  |             |                 |
| IO-Link revision                                                                                   | 1.1                                                                                                |             |                 |
| SDCI standard                                                                                      | IEC 61131-9                                                                                        |             |                 |
| IO-Link device ID                                                                                  | 402 d / 00 01 92 h                                                                                 |             |                 |
| Profiles                                                                                           | Smart Sensor: Process Data Variable; Device Identification, Device Diagnosis                       |             |                 |
| SIO mode                                                                                           | yes                                                                                                |             |                 |
| Required master port class                                                                         | A                                                                                                  |             |                 |
| Process data analogue                                                                              | 1                                                                                                  |             |                 |
| Process data binary                                                                                | 2                                                                                                  |             |                 |
| Min. process cycle time [ms]                                                                       | 2.3                                                                                                |             |                 |
| Environment                                                                                        |                                                                                                    |             |                 |
| Ambient temperature [°C]                                                                           | -25...80                                                                                           |             |                 |
| Storage temperature [°C]                                                                           | -40...100                                                                                          |             |                 |
| Protection                                                                                         | IP 65 / IP 67                                                                                      |             |                 |
| Tests / approvals                                                                                  |                                                                                                    |             |                 |
| Pressure equipment directive                                                                       | Sound engineering practice                                                                         |             |                 |
| EMC                                                                                                | DIN EN 61000-6-2<br>DIN EN 61000-6-3                                                               |             |                 |
| Shock resistance                                                                                   | DIN EN 60068-2-27 50 g (11 ms)                                                                     |             |                 |
| Vibration resistance                                                                               | DIN EN 60068-2-6 20 g (10...2000 Hz)                                                               |             |                 |
| MTTF [Years]                                                                                       | 224.01                                                                                             |             |                 |
| UL approval number                                                                                 | J001                                                                                               |             |                 |
| Mechanical data                                                                                    |                                                                                                    |             |                 |
| Process connection                                                                                 | G ¼ I                                                                                              |             |                 |
| Materials (wetted parts)                                                                           | 1.4404; ceramics; FKM                                                                              |             |                 |
| Housing materials                                                                                  | 1.4404; PBT+PC-GF 30; PBT-GF 20; PC                                                                |             |                 |
| Switching cycles min.                                                                              | 100 million                                                                                        |             |                 |
| Tightening torque [Nm]                                                                             | 25...35 (recommended tightening torque²)                                                           |             |                 |
| Weight [kg]                                                                                        | 0.234                                                                                              |             |                 |

PN7093 - Electronic pressure monitor - eclass: 27201302 / 27-20-13-02

|                                                                                            |                                                                                                                                                                                                                                |
|--------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Displays / operating elements                                                              |                                                                                                                                                                                                                                |
| Display                                                                                    | Display unit     3 x LED green (bar, psi, MPa)<br>Switching status 2 x LED yellow<br>4-digit alphanumeric display / alternating indication<br>Measured values of red and green                                                 |
| Electrical connection                                                                      |                                                                                                                                                                                                                                |
| Connection                                                                                 | M12 connector; Gold-plated contacts                                                                                                                                                                                            |
| <b>Wiring</b>                                                                              |                                                                                                                                                                                                                                |
| Core colours                                                                               |                                                                                                                                               |
| BK     black                                                                               |                                                                                                                                                                                                                                |
| BN     brown                                                                               |                                                                                                                                                                                                                                |
| BU     blue                                                                                |                                                                                                                                                                                                                                |
| WH     white                                                                               |                                                                                                                                                                                                                                |
| OUT1: switching output or IO-Link<br>OUT2: switching output<br>Colours to DIN EN 60947-5-2 |                                                                                                                                                                                                                                |
| Remarks                                                                                    |                                                                                                                                                                                                                                |
| Remarks                                                                                    | 1) to EN50178, SELV, PELV<br>*) BFSL = Best Fit Straight Line / LS = Limit Value Setting<br>**) with temperature fluctuations < 10 K<br>***) in% of the span / 6 months<br>2) Depends on lubrication, seal and pressure rating |
| Pack quantity                                                                              | [piece] 1                                                                                                                                                                                                                      |