

Part No.

LC10-GL2M

LC10 pressure gauge, 300 psi / 20 bar / 2 MPa, 1/4" Male NPT bottom connection

The LC10 is a robust device that measures and displays pressure readings on a large, backlit screen. The LC10 has the ability to show High and Low pressure values on-screen, change between 15 different engineering units or add custom engineering units. The included PC FieldLab Desktop software can be used for calibration, testing and live viewing of pressure.



LC10-GL2M

Specs/Attributes

Battery Count	2
Battery Life	1500 Hours
Battery Type	AA Alkaline (IEC-LR6)
Calibration Certificate	Not included
Certifications	Certified to CSA Standard C22.2 No. 61010-1, Conforms to UL / IEC / EN / AS Standard No. 61010-1, Complies with Pressure Equipment Directive 2014/68/EU, Complies with Low Voltage Directive 2014/35/EU, Complies with Electromagnetic Compatibility Directive 2014/30/EU
Country of origin	USA
Datalogging	PC based (via USB)
Electrical Rating	50 mA @ 5 VDC
Harmonized Code	9026.20.0000
Ingress Protection	IP67 (1 meter water submersion for 30 minutes)
LCD Display	2.4 in / 61 mm segmented LCD Display
Materials	ABS / Polycarbonate Blend, Powder Coated Aluminum
Max Operating Temperature	120 °F / 50 °C
Min Operating Temperature	-4 °F / -20 °C
Operating Altitude (max)	10,000 ft (3050 m)
Panel Mount	No
Primary Power	Battery Power

Specs/Attributes

Process Connection Location	Bottom mount
Protection Class	Pollution Degree 2 (UL / IEC 61010-1)
Relative Humidity	0% to 90% (-10 to 35°C) , 0% to 70% (35 to 50°C)
Sensor Type	High Precision MEMS
Temperature Compensation	None
USB Connection	USB (Micro B)
Wetted Materials	316 Stainless Steel
Weight	12.6 oz / 355 grams
Dimensions	H: 1.75 in (4.45 cm) x W: 3.4 in (8.64 cm) x D: 4.1 in (10.41 cm)

Sensor A (Bottom)

Measurement Type	Gauge Pressure
Max Pressure	300 PSI / 20 bar / 2.00 MPa
Wetted Materials	316 Stainless Steel
Wrench Size	7/8 In 23 mm
Max Storage Temperature	165 °F / 75 °C
Min Storage Temperature	-40 °F / -40 °C
Accuracy - Pressure Measurement	+/- 0.25% of Full Scale (ASME B40.100 Grade 3A/ISO Class 0.25)
Burst Pressure	1200 PSI / 83 bar / 8.30 MPa
Media Compatibility	Air, Alcohol, Antifreeze, Ethylene Glycol, Hydraulic Oil, Inert Gas, Light motor oil, Mineral Oil, Natural Gas, Petroleum Based Oil, Ralston Calibration Oil, Skydrol, Transmission fluid, Water, Windshield washer fluid, Oxygen (If Oxygen cleaned)
Country of origin	USA
Max Operating Temperature	120 °F / 50 °C
Min Operating Temperature	-4 °F / -20 °C
Process Connection	1/4" Male NPT
Engineering Units	atm, bar, cmH2O @4°C, inH2O @39°C, kPa, MPa, mbar, psi, inHg @39°F, kgf / cm^2, mmHg @0°C, Torr, ftH2O @39°F, cmHg @ 0°C, oz / in^2
Sensor Type	Pressure Sensor