

Part No.

LC20-GZ2H-00-B1

LC20 pressure gauge, 30,000 psi / 200 MPa, 1/4" Female High Pressure bottomconn., Bluetooth radio

The LC20 is a robust device that measures and displays pressure readings on a large, backlit screen. The LC20 has the ability to show High and Low pressure values on-screen, change between 15 different engineering units or add custom engineering units. The included PC FieldLab Desktop software can be used for calibration, testing and live viewing of pressure.



LC20-GZ2H-00-B1

Specs/Attributes

Battery Count	2
Battery Life	1000 Hours
Battery Type	AA Alkaline (IEC-LR6)
Bluetooth Radio Installed	Yes
Calibration Certificate	ISO 17025:2017 Accredited
Certifications	Certified to CSA Standard C22.2 No. 61010-1, Complies with Pressure Equipment Directive 2014/68/EU, Complies with Low Voltage Directive 2014/35/EU, Complies with Electromagnetic Compatibility Directive 2014/30/EU
Contains Wireless Module	Yes
Country of origin	USA
Datalogging	870 Readings (onboard)
Electrical Rating	50 mA @ 5 VDC
Harmonized Code	9026.20.0000
Ingress Protection	IP67 (1 meter water submersion for 30 minutes)
LCD Display	2.4 in / 61 mm segmented LCD Display
Materials	ABS / Polycarbonate Blend, Powder Coated Aluminum

Specs/Attributes

Max Operating Temperature	120 °F / 50 °C
Min Operating Temperature	-4 °F / -20 °C
Panel Mount	No
Primary Power	Battery Power
Process Connection Location	Bottom mount
Protection Class	Pollution Degree 2 (UL / IEC 61010-1)
Radio Approvals	FCC ID 2AA9B04, IC ID 12208A-04, Japan ID 210-107153, Korea - Clause 3, Article 58-2 of Radio Waves Act
Radio Type	Bluetooth 5 LE
Temperature Compensation	None
USB Connection	USB (Micro B)
Wetted Materials	316 Stainless Steel
Wireless	Bluetooth
Wireless Range	330 ft / 100 m
Connector End 1	1/4" Male NPT (ASME B1.20.1)
Connector End 2	9/16-18 (1/4" HF4) Female High Pressure
Weight	12.6 oz / 355 grams
Dimensions	H: 1.75 in (4.45 cm) x W: 3.4 in (8.64 cm) x D: 4.1 in (10.41 cm)

Sensor A (Bottom)

Max Storage Temperature	165 °F / 75 °C
Min Storage Temperature	-40 °F / -40 °C
Burst Pressure	120000 PSI / 8275 bar / 830 MPa
Max Operating Temperature	120 °F / 50 °C
Min Operating Temperature	-4 °F / -20 °C
Wrench Size	7/8 In 23 mm
Measurement Type	Gauge Pressure
Max Pressure	30000 PSI / 2070 bar / 205 MPa
Wetted Materials	17-4 Stainless Steel
Engineering Units	atm, bar, MPa, psi, inHg @39°F, kgf / cm ² , ftH ₂ O @39°F, cmHg @ 0°C
Media Compatibility	Air, Alcohol, Antifreeze, Ethylene Glycol, Hydraulic Oil, Inert Gas, Light motor oil, Mineral Oil, Natural Gas, Petroleum Based Oil, Ralston Calibration Oil, Skydrol, Transmission fluid, Water, Windshield washer fluid

Sensor A (Bottom)

Accuracy - Pressure Measurement	+/- 0.1% of Full Scale (ASME B40.100 Grade 4A/ISO Class 0.1)
Materials	Stainless Steel
Sensor Type	Pressure Sensor
Process Connection	9/16-20 Female High Pressure (1/4 HP)
Max Vacuum	0.00 InHg / 0.0 kPa