

Part No.

# LC30-GA2M-00-00

LC30 panel mount vacuum gauge, 30Hg / 780 mmHg, 1/4"  
Male NPT back connection

The LC30 is a robust device that measures and displays pressure readings on a large, backlit screen. It is AC powered with a battery backup. The LC30 has the ability to show High and Low pressure values on-screen, change between 15 different engineering units or add custom engineering units. The included PC FieldLab Desktop software can be used for calibration, testing and logging pressure.



LC30-GA2M-00-00

## Specs/Attributes

|                           |                                                                                                                                                                                                                      |
|---------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Backup Power              | AAA Alkaline (IEC-LR03)                                                                                                                                                                                              |
| Battery Count             | 2                                                                                                                                                                                                                    |
| Battery Life              | 1000 Hours                                                                                                                                                                                                           |
| Calibration Certificate   | ISO 17025:2017 Accredited                                                                                                                                                                                            |
| Certifications            | Certified to CSA Standard C22.2 No. 61010-1, Complies with Pressure Equipment Directive 2014/68/EU, Complies with Low Voltage Directive 2014/35/EU, Complies with Electromagnetic Compatibility Directive 2014/30/EU |
| Country of origin         | USA                                                                                                                                                                                                                  |
| Datalogging               | PC based (via USB)                                                                                                                                                                                                   |
| Electrical Rating         | 50 mA @ 5 VDC                                                                                                                                                                                                        |
| Harmonized Code           | 9026.20.0000                                                                                                                                                                                                         |
| Ingress Protection        | IP67 (1 meter water submersion for 30 minutes)                                                                                                                                                                       |
| LCD Display               | 2.4 in / 61 mm segmented LCD Display                                                                                                                                                                                 |
| Materials                 | ABS / Polycarbonate Blend, Powder Coated Aluminum                                                                                                                                                                    |
| Max Operating Temperature | 120 °F / 50 °C                                                                                                                                                                                                       |
| Media Compatibility       | Inert Gas, Natural Gas, Petroleum Based Oil, Water                                                                                                                                                                   |
| Min Operating Temperature | -4 °F / -20 °C                                                                                                                                                                                                       |
| Operating Altitude (max)  | 10,000 ft (3050 m)                                                                                                                                                                                                   |
| Panel Mount               | Yes                                                                                                                                                                                                                  |
| Power Input               | 90-264 VAC, 50-60 Hz                                                                                                                                                                                                 |
| Primary Power             | AC Mains Power                                                                                                                                                                                                       |

## Specs/Attributes

|                             |                                                                   |
|-----------------------------|-------------------------------------------------------------------|
| Process Connection          | 1/4" Male NPT (ASME B1.20.1)                                      |
| Process Connection Location | Back mount                                                        |
| Protection Class            | Pollution Degree 2 (UL / IEC 61010-1)                             |
| Relative Humidity           | 0% to 90% (-10 to 35°C) , 0% to 70% (35 to 50°C)                  |
| Temperature Compensation    | None                                                              |
| USB Connection              | USB (Micro B)                                                     |
| W1 Radio Installed          | No                                                                |
| Wetted Materials            | 316 Stainless Steel                                               |
| Wireless                    | None                                                              |
| Weight                      | 12.6 oz / 355 grams                                               |
| Dimensions                  | H: 1.75 in (4.45 cm) x W: 3.4 in (8.64 cm) x D: 4.1 in (10.41 cm) |

## Sensor A (Back)

|                                 |                                                                                                                                                                                                                                                       |
|---------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Engineering Units               | atm, bar, cmH2O @4°C, inH2O @39°C, kPa, mbar, psi, inHg @39°F, kgf / cm^2, mmHg @0°C, mmH2O @4°C, ftH2O @39°F, cmHg @ 0°C, oz / in^2                                                                                                                  |
| Measurement Type                | Gauge Vacuum                                                                                                                                                                                                                                          |
| Sensor Type                     | Pressure Sensor                                                                                                                                                                                                                                       |
| Max Storage Temperature         | 165 °F / 75 °C                                                                                                                                                                                                                                        |
| Min Operating Temperature       | -4 °F / -20 °C                                                                                                                                                                                                                                        |
| Min Storage Temperature         | -40 °F / -40 °C                                                                                                                                                                                                                                       |
| Max Vacuum                      | 30 InHg / 101.6 kPa                                                                                                                                                                                                                                   |
| Country of origin               | USA                                                                                                                                                                                                                                                   |
| Burst Pressure                  | 20 PSI / 1.4 bar / 140 kPa                                                                                                                                                                                                                            |
| Wrench Size                     | 7/8 In<br>23 mm                                                                                                                                                                                                                                       |
| Media Compatibility             | Air, Alcohol, Antifreeze, Ethylene Glycol, Hydraulic Oil, Inert Gas, Light motor oil, Mineral Oil, Natural Gas, Petroleum Based Oil, Ralston Calibration Oil, Skydrol, Transmission fluid, Water, Windshield washer fluid, Oxygen (If Oxygen cleaned) |
| Accuracy - Pressure Measurement | +/- 0.1% of Full Scale (ASME B40.100 Grade 4A/ISO Class 0.1)                                                                                                                                                                                          |
| Wetted Materials                | 316 Stainless Steel                                                                                                                                                                                                                                   |
| Max Operating Temperature       | 120 °F / 50 °C                                                                                                                                                                                                                                        |
| Process Connection              | 1/4" Male NPT                                                                                                                                                                                                                                         |
| Max Pressure                    | 0.00 PSI / 0.00 mbar / 0.00 kPa                                                                                                                                                                                                                       |