

Part No.

QTVC-KIT5-GR

QTVC volume controller, 3000 PSI LC20 digital gauge, 6ft, 3ft hoses, (2) 1/4in MNPT process conn.

Connect to and calibrate both very low or high pressure instrumentation using included volume controller and pressure gauge



QTVC-KIT5-GR

Included Items

- Volume Controller - QTVC Volume Controller (QTVC)
- Pressure Reference - LC20 pressure gauge, 3000 psi / 20 MPa, 1/4" Male NPT bottom connection (LC20-GR2M-00-00)
- Reference Connection - 1/4" female NPT x female Quick-test, no check-valve, brass (QTHA-2FBA)
- Process Connection (Qty 2) - 1/4" male NPT x male Quick-test, no check-valve, brass (QTHA-2MB0)
- Hose 1 - Quick-test 6900 psi hose, brass hose ends, 6 ft (1.83 m) long (QTQT-HOS-6ft)
- Hose 2 - Quick-test 6900 psi hose, brass hose ends, 3 ft (92 cm) long (QTQT-HOS-3ft)

Specs/Attributes

Materials	Anodized Aluminum, Brass, Plated Steel, Stainless Steel
Seal Materials	Buna-N, Delrin, Teflon
Max Pressure	3000 PSI / 200 bar / 20 MPa
Max Vacuum	10 InHg / 33.9 kPa
Min Operating Temperature	0 °F / -18 °C
Max Operating Temperature	130 °F / 54 °C
Country of origin	USA

Specs/Attributes

Hose 1	Quick-test Hose, Brass ends, 6ft / 1.9m long
Hose 2	Quick-test Hose, Brass ends, 3ft / 0.9m long
Pressure Reference	Digital pressure gauge, 3000 PSIG Pressure
Process Connection	1/4" Male NPT
Reference Connection	1/4" Female NPT
Weight	6.51 lbs / 2.95 kg
Dimensions	H: 10.5 in (26.67 cm) x W: 8.5 in (21.59 cm) x D: 7.38 in (18.75 cm)

Volume Controller QTVC

Harmonized Code	9032.81.0060
Inlet Port	Male Quick-test
Outlet Port	Male Quick-test, Male Quick-test with cap and chain
Max Pressure	3000 PSI / 200 bar / 20 MPa
Max Vacuum	10 InHg / 33.9 kPa
Min Operating Temperature	0 °F / -18 °C
Max Operating Temperature	130 °F / 54 °C
Mechanical Rotation	42 turns (pressure balanced)
Materials	Anodized Aluminum, Brass, Powder Coated Steel, Stainless Steel
Media Compatibility	Air, Inert Gas, Natural Gas
Seal Materials	Buna-N, Delrin, Teflon
Country of origin	USA
Fine Adjustment Resolution	0.0005 psi / 3 Pa
Weight	3.70 lbs / 1.68 kg
Dimensions	H: 6.8 in (17.27 cm) x W: 8.5 in (21.59 cm) x D: 6.6 in (16.76 cm)

Pressure Reference LC20-GR2M-00-00

Battery Count	2
Battery Life	1000 Hours
Battery Type	AA Alkaline (IEC-LR6)
Bluetooth Radio Installed	No
Calibration Certificate	ISO 17025:2017 Accredited
Certifications	Certified to CSA Standard C22.2 No. 61010-1, Complies with Pressure Equipment Directive 2014/68/EU, Complies with Low Voltage Directive 2014/35/EU, Complies with Electromagnetic Compatibility Directive 2014/30/EU
Country of origin	USA
Datalogging	PC based (via USB)
Electrical Rating	50 mA @ 5 VDC

Pressure Reference LC20-GR2M-00-00

Harmonized Code	9026.20.0000
Ingress Protection	IP67 (1 meter water submersion for 30 minutes)
LCD Display	2.4 in / 61 mm segmented LCD Display
Materials	ABS / Polycarbonate Blend, Powder Coated Aluminum
Max Operating Temperature	120 °F / 50 °C
Min Operating Temperature	-4 °F / -20 °C
Panel Mount	No
Primary Power	Battery Power
Process Connection	1/4" Male NPT (ASME B1.20.1)
Process Connection Location	Bottom mount
Protection Class	Pollution Degree 2 (UL / IEC 61010-1)
Temperature Compensation	None
USB Connection	USB (Micro B)
W1 Radio Installed	No
Wetted Materials	316 Stainless Steel
Wireless	None
Weight	12.6 oz / 355 grams
Dimensions	H: 1.75 in (4.45 cm) x W: 3.4 in (8.64 cm) x D: 4.1 in (10.41 cm)

Reference Connection QTHA-2FBA

Country of origin	USA
Has Check Valve	No
Materials	Brass
Max Operating Temperature	225 °F / 105 °C
Max Pressure	5000 PSI / 350 bar / 35 MPa
Max Vacuum	0.00 InHg / 0.0 kPa
Wrench Size	3/4 In 19 mm
Connector End 1	1/4" Female NPT (ASME B1.20.1)
Connector End 2	Female Quick-test
Weight	2.05 oz / 58 grams
Dimensions	H: 1.52 in (3.86 cm) x W: 0.75 in (1.91 cm) x D: 0.75 in (1.91 cm)

Process Connection (Qty 2) QTHA-2MB0

Burst Pressure	20000 PSI / 1380 bar / 140 MPa
Country of origin	USA

Process Connection (Qty 2) QTHA-2MB0

Materials	Brass
Max Operating Temperature	225 °F / 105 °C
Max Pressure	5000 PSI / 350 bar / 35 MPa
Max Vacuum	0.00 InHg / 0.0 kPa
Min Operating Temperature	0 °F / -18 °C
Seal Materials	Buna-N
Wrench Size	9/16 In 15 mm
Connector End 1	1/4" Male NPT (ASME B1.20.1)
Connector End 2	Male Quick-test
Weight	1.09 oz / 31 grams
Dimensions	H: 1.29 in (3.28 cm) x W: 0.56 in (1.42 cm) x D: 0.56 in (1.42 cm)

Hose 1 QTQT-HOS-6ft

Burst Pressure	27000 PSI / 1860 bar / 185 MPa
Color	Silver
Country of origin	USA
Fluid Media	Air, Inert Gas, Natural Gas, Petroleum Based Oil, Water
Hose Length	6 ft / 1.83 m
Inner Diameter	0.08 In / 3.00 mm
Length	6 ft / 2.00 m
Materials	Brass
Max Operating Temperature	140 °F / 60 °C
Max Pressure	6900 PSI / 475 bar / 48 MPa
Max Vacuum	-30.00 InHg / -101.6 kPa
Media Compatibility	Air, Inert Gas, Natural Gas, Petroleum Based Oil, Water
Min Operating Temperature	-40 °F / -40 °C
Minimum Bend Radius	1.00 In / 26 mm
Outer Diameter	0.20 In / 6.00 mm
Type	QT
Weight	3.19 oz / 90 grams

Hose 2 QTQT-HOS-3ft

Burst Pressure	27000 PSI / 1860 bar / 185 MPa
Color	Silver
Country of origin	USA

Hose 2 QTQT-HOS-3ft

Fluid Media	Air, Inert Gas, Natural Gas, Petroleum Based Oil, Water
Hose Length	3ft / 0.91 m
Inner Diameter	0.08 In / 3.00 mm
Length	3 ft / 92 cm
Materials	Brass
Max Operating Temperature	140 °F / 60 °C
Max Pressure	6900 PSI / 475 bar / 48 MPa
Max Vacuum	-30.00 InHg / -101.6 kPa
Media Compatibility	Air, Inert Gas, Natural Gas, Petroleum Based Oil, Water
Min Operating Temperature	-40 °F / -40 °C
Minimum Bend Radius	1.00 In / 26 mm
Outer Diameter	0.20 In / 6.00 mm
Type	QT
Weight	2.68 oz / 76 grams