




UGT208

UG-02200E2KG/US

Ultrasonic sensors



- 1: LEDs
2: teach button



Product characteristics

Ultrasonic diffuse-reflection sensor

Threaded type

M18 x 1

Connector

Teach function

Electrical data

Electrical design	DC PNP
Operating voltage [V]	10...30 DC
Current consumption [mA]	55
Protection class	III
Reverse polarity protection	yes
Power-on delay time [s]	< 0.3
Converter frequency [kHz]	200

Inputs

Teach	yes
-------	-----

Outputs

Output function	1 x NO / NC programmable + 1 x voltage output
Current rating [mA]	100
Voltage drop [V]	2.2
Short-circuit protection	yes
Overload protection	yes
Analogue output	
voltage output [V]	0...10
Min. load resistance [Ω]	3000
Switching frequency [Hz]	2

Range

Sensing range [mm]	2200
blind zone [mm]	200




UGT208

UG-02200E2KG/US

Ultrasonic sensors

Response curve



1: Distance; 2: Sound beam; 3: Target Ø 25 mm; 4: Target 200 x 200 mm

Angle of aperture [°]

8 ± 2

Max. deviation from the 90° angle
sensor / object [°]

± 4

Accuracy / deviations

Notes on the accuracy / deviation

The indicated values are reached after a warm-up time of ≥ 20 minutes

Temperature compensation

yes

Hysteresis [%]

1

Switch-point drift [%]

± 2

Linearity error [%]

1

Resolution [mm]

< 3

Repeatability [%]

0.5

Environment

Ambient temperature [°C]

-20...70

Protection

IP 67

Tests / approvals

EMC

EN 61000-4-2 ESD: 4 kV CD / plastics
8 kV AD / metal
EN 61000-4-3 HF radiated: 3 V/m
EN 61000-4-4 Burst: 2 kV
EN 61000-4-6 HF conducted: 3 V
EN 55011: class A

Vibration resistance

(10-55) Hz 1 mm amplitude,
oscillation period 5 min., 30 min.
per axis at resonance or 55 Hz

Shock resistance

EN 60068-2-27 Ea yes

Mechanical data

Housing materials

PBT; polyamide; Epoxid-Glaskeramik

Weight [kg]

0.065

Displays / operating elements

Display

Switching status 2 LED yellow
Echo LED 1 LED green

Electrical connection

Connection

M12 connector



Wiring



UGT208

UG-02200E2KG/US

Ultrasonic sensors



Accessories	
Accessories (included)	2 fixing nuts (plastic); 2 rubber washers
Remarks	
Remarks	cULus - Class 2 source required
Pack quantity	[piece] 1